


Rillenkugellager einreihig ZKLN3062-2Z-INA - ZKLN3062-2Z-INA


<https://www.123kugellager.at/kugellager-gehauselager/rillenkugellager/einreihig/zkln3062-2z-ina>

Axial angular contact ball bearings ZKLN3062-2Z
double direction, gap seats on both sides



d	30 mm	Tolerance: -0.005
D	62 mm	Tolerance: -0.010
B	28 mm	Tolerance: -0.25
α	60 °	Contact angle
D_{h max}	53 mm	
d₁	45.5 mm	
d_{2 max}	40 mm	
r_{1 max}	0.6 mm	
r_{2 max}	0.3 mm	
m	0.39 kg	Mass
C_a	29500 N	Basic dynamic load rating, axial
C_{0a}	49000 N	Basic static load rating, axial
n_{0a}	4300 1/min	Limiting speed for grease lubrication
M_{0a}	0.25 Nm	Bearing frictional torque
Δi_{0a}	300 N/μm	Axial rigidity
Δi_{0a}	300 N/mmrad	Tilting rigidity
M_r	0.73 kg x cm ²	Mass moment of inertia for rotating inner ring
r₁	2.5 μm	Axial runout
		The axial runout data for screw drive bearing arrangements are based on the rotating inner ring.
		ZK30 Designation of recommended INA locknut
		AK30 Designation of recommended INA locknut
		Locknuts not included in delivery.
M_t	32 Nm	Tightening torque
		Only valid in conjunction with INA-precision locknuts
	10451 N	Axial preload force

Design of adjacent construction



Design of adjacent construction

PRODUKTMERKMALE

Marke	INA
N° Ean13	3663952334899
Innendurchmesser	30 mm
Wasserdichtheit	-
Außendurchmesser	62 mm
Dicke	28 mm
Verpackung	-

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE