

Pendelkugellager 1214-K-TVH-C3-H214-FAG - 1214-K-TVH-C3-H214-FAG

<https://www.123kugellager.at/kugellager-gehauselager/rillenkugellager/pendelkugellager/1214-k-tvh-c3-h214-fag>

Self-aligning ball bearings 1214-K-TVH-C3 + H214
main dimensions to DIN 630 and DIN 9415, with tapered bore and adapter sleeve

| | |
|-------------|---|
| d_{int} | 60 mm |
| D | 125 mm |
| B | 24 mm |
| B_{2min} | 5 mm |
| c | 14 mm |
| D_1 | 106.6 mm |
| D_{1max} | 116 mm |
| D_{21} | 92 mm |
| d | 70 mm |
| d_1 | 87.7 mm |
| d_{21max} | 75 mm |
| d_{21min} | 75 mm |
| I | 41 mm |
| f_{1max} | 1.8 mm |
| f_{11} | H214 Mass, adapter sleeve |
| m | 1.23 kg Mass |
| m_1 | 0.63 kg Mass, adapter sleeve |
| C | 35000 N Basic dynamic load rating, radial |
| e | 0.19 |
| Y_1 | 3.36 |
| Y_2 | 5.21 |
| C_{10} | 13700 N Basic static load rating, radial |
| Y_0 | 3.52 |
| n_0 | 6000 1/min Limiting speed |
| n_B | 7900 1/min Reference speed |
| C_{10} | 800 N Fatigue limit load, radial |

PRODUKTMERKMALE

| | |
|------------------|---------------|
| Marke | FAG |
| N° Ean13 | 3663952346250 |
| Innendurchmesser | 60 mm |
| Außendurchmesser | 125 mm |
| Dicke | 24 mm |
| Verpackung | 1 |

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE