



Pendelkugellager 1219-K-M-C3-H219-FAG - 1219-K-M-C3-H219-FAG

<https://www.123kugellager.at/kugellager-gehauselager/rillenkugellager/pendelkugellager/1219-k-m-c3-h219-fag>

Self-aligning ball bearings 1219-K-M-C3 + H219
main dimensions to DIN 630 and DIN 5415, with tapered bore and adapter sleeve

d _{min}	85 mm
D	170 mm
B	32 mm
B _{min}	7 mm
c	19 mm
D ₁	149.2 mm
D _{2 max}	158 mm
D _{2 min}	125 mm
d	95 mm
d ₁	120.5 mm
d _{2 max}	107 mm
d _{2 min}	100 mm
l	55 mm
f _{min}	2.1 mm
H219	Mass, adapter sleeve
m	3.28 kg Mass
m ₁	1.39 kg Mass, adapter sleeve
C	64000 N Basic dynamic load rating, radial
e	0.17
Y ₁	3.73
Y ₂	5.78
C ₀	27000 N Basic static load rating, radial
Y ₀	3.91
n _C	6000 1/min Limiting speed
n _R	6200 1/min Reference speed
C ₀	1450 N Fatigue limit load, radial

PRODUKTMERKMALE

Marke	FAG
N° Ean13	3663952346304
Innendurchmesser	85 mm
Außendurchmesser	170 mm
Dicke	32 mm
Verpackung	1

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE