


Zylinderrollenlager N215-E-TVP2-FAG - N215-E-TVP2-FAG

<https://www.123kugellager.at/kugellager-gehauselager/zylinderrollenlager/zylinder/n215-e-tvp2-fag>

Cylindrical roller bearings N215-E-TVP2
main dimensions to DIN 5412-1, non-loading bearing, separable, with cage



d	75 mm
D	130 mm
B	25 mm
D _{1 max}	121 mm
D _{1 min}	120 mm
D _{2 max}	117 mm
d ₁	94.8 mm
d _{2 max}	86 mm
E	118.8 mm
F	88.8 mm
F _{1 min}	1.5 mm
F _{2 max}	1.5 mm
F _{3 min}	1.5 mm
F _{4 max}	1.5 mm
F _{5 min}	1.5 mm
F _{6 max}	1.5 mm
F _{7 min}	1.5 mm
F _{8 max}	1.5 mm
F _{9 min}	1.5 mm
F _{10 max}	1.5 mm
F _{11 min}	1.5 mm
F _{12 max}	1.5 mm
F _{13 min}	1.5 mm
F _{14 max}	1.5 mm
F _{15 min}	1.5 mm
F _{16 max}	1.5 mm
F _{17 min}	1.5 mm
F _{18 max}	1.5 mm
F _{19 min}	1.5 mm
F _{20 max}	1.5 mm
F _{21 min}	1.5 mm
F _{22 max}	1.5 mm
F _{23 min}	1.5 mm
F _{24 max}	1.5 mm
F _{25 min}	1.5 mm
F _{26 max}	1.5 mm
F _{27 min}	1.5 mm
F _{28 max}	1.5 mm
F _{29 min}	1.5 mm
F _{30 max}	1.5 mm
F _{31 min}	1.5 mm
F _{32 max}	1.5 mm
F _{33 min}	1.5 mm
F _{34 max}	1.5 mm
F _{35 min}	1.5 mm
F _{36 max}	1.5 mm
F _{37 min}	1.5 mm
F _{38 max}	1.5 mm
F _{39 min}	1.5 mm
F _{40 max}	1.5 mm
F _{41 min}	1.5 mm
F _{42 max}	1.5 mm
F _{43 min}	1.5 mm
F _{44 max}	1.5 mm
F _{45 min}	1.5 mm
F _{46 max}	1.5 mm
F _{47 min}	1.5 mm
F _{48 max}	1.5 mm
F _{49 min}	1.5 mm
F _{50 max}	1.5 mm
F _{51 min}	1.5 mm
F _{52 max}	1.5 mm
F _{53 min}	1.5 mm
F _{54 max}	1.5 mm
F _{55 min}	1.5 mm
F _{56 max}	1.5 mm
F _{57 min}	1.5 mm
F _{58 max}	1.5 mm
F _{59 min}	1.5 mm
F _{60 max}	1.5 mm
F _{61 min}	1.5 mm
F _{62 max}	1.5 mm
F _{63 min}	1.5 mm
F _{64 max}	1.5 mm
F _{65 min}	1.5 mm
F _{66 max}	1.5 mm
F _{67 min}	1.5 mm
F _{68 max}	1.5 mm
F _{69 min}	1.5 mm
F _{70 max}	1.5 mm
F _{71 min}	1.5 mm
F _{72 max}	1.5 mm
F _{73 min}	1.5 mm
F _{74 max}	1.5 mm
F _{75 min}	1.5 mm
F _{76 max}	1.5 mm
F _{77 min}	1.5 mm
F _{78 max}	1.5 mm
F _{79 min}	1.5 mm
F _{80 max}	1.5 mm
F _{81 min}	1.5 mm
F _{82 max}	1.5 mm
F _{83 min}	1.5 mm
F _{84 max}	1.5 mm
F _{85 min}	1.5 mm
F _{86 max}	1.5 mm
F _{87 min}	1.5 mm
F _{88 max}	1.5 mm
F _{89 min}	1.5 mm
F _{90 max}	1.5 mm
F _{91 min}	1.5 mm
F _{92 max}	1.5 mm
F _{93 min}	1.5 mm
F _{94 max}	1.5 mm
F _{95 min}	1.5 mm
F _{96 max}	1.5 mm
F _{97 min}	1.5 mm
F _{98 max}	1.5 mm
F _{99 min}	1.5 mm
F _{100 max}	1.5 mm
m	3720 kg Mass
C	155000 N Basic dynamic load rating, radial
C ₀	157000 N Basic static load rating, radial
n _c	6000 1/min Limiting speed
n _r	4000 1/min Reference speed
C ₁₀	27500 N Fatigue limit load, radial

PRODUKTMERKMALE

Marke	FAG
N° Ean13	3663952351025
Innendurchmesser	75 mm
Außendurchmesser	130 mm
Dicke	25 mm
Verpackung	1

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE