Nadelhülsenlager
TLAM1812-IKO - TLAM1812-IKO

https://www.123kugellager.at/kugellager-gehauselager/nadellager/nadelhulsenlager/tlam1812-iko



IKO

SHELL TYPE NEEDLE ROLLER BEARINGS

TAM TLAM

Shaft dia. mm	Identification number: Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g
18	—	—	—	—			TLAM 1812	13.7	—	—

Boundary dimensions mm F_w	D	C	t_2 Max.	Standard mounting dimensions mm: Shaft dia. h6 Max.	Shaft dia. h6 Min.	Housing bore dia. J7 Max.	Housing bore dia. J7 Min.	Housing bore dia. N7 Max.	Housing bore dia. N7 Min.	Basic dynamic load rating C N	Basic static load rating C_0 N	Allowable rotational speed(*) rpm	Assembled inner ring
18	24	12	1.3	18.000	17.989	—	—	23.993	23.972	8 230	11 500	20 000	IRT 1512

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

123BEARING

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952352978
Innendurchmesser	18 mm
Außendurchmesser	24 mm
Dicke	12 mm
Verpackung	1

kontakt@123kugellager.at
+49 (0) 800 001 076 6
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE