


Nadelhülsenlager TA6030-Z-IKO - TA6030-Z-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/nadelhulsenlager/ta6030-z-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS



Shaft dia. mm	Identification number								
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g
60	TA 6030 Z	191	—	—	—	—	—	—	—

Boundary dimensions mm	Standard reporting dimensions mm						Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ^(*) rpm	Assembled inner ring			
	Shaft dia. H7	Shaft dia. h8	Housing bore dia. H7	Housing bore dia. h7	Max.	Min.							
F _w D C	72	30	3.4	60.000	59.981	72.018	71.988	—	—	66 300	139 000	5 000	IRT 5030

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 80% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952357409
Innendurchmesser	60 mm
Außendurchmesser	72 mm
Dicke	30 mm
Verpackung	1

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE