


# Nadelhülsenlager TAW6212-Z-IKO - TAW6212-Z-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/nadelhulsenlager/taw6212-z-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**



Shaft dia. mm	Identification number								
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g
62	TA 6212 Z	78	—	—	—	—	—	—	—

Boundary dimensions mm		Standard reporting dimensions mm						Basic dynamic load rating	Basic static load rating	Allowable rotational speed <sup>(*)</sup>	Assembled inner ring		
F <sub>w</sub>	D	C	t <sub>2</sub> Max.	Shaft dia. H7 Max. Min.	Housing bore dia. H7 Max. Min.	N7 Max. Min.	C	C <sub>0</sub>	N	rpm	IRT 5212		
62	74	12	3.4	62.000	61.981	74.018	73.988	—	—	20 100	30 300	4 500	IRT 5212

Note(\*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 80% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952357447
Innendurchmesser	62 mm
Außendurchmesser	74 mm
Dicke	12 mm
Verpackung	1

[kontakt@123kugellager.at](mailto:kontakt@123kugellager.at)

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE