


## Nadelhülsenlager YB55-IKO - YB55-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/nadelhulsenlager/yb55-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g				
	Standard	Mass (Ref.) g	Closed end														
7.938 ( $\frac{5}{16}$ )	—	—	—	YB	55	3.8	—	—	—	—	—	—	—				
Boundary dimensions		mm (inch)		Standard mounting dimensions				mm		Basic dynamic load rating		Basic static load rating		Allowable rotational speed <sup>(1)</sup>		Assembled inner ring	
$F_w$	$D$	$C$	$b_2$	Shaft dia. h8		Housing bore dia. J7		$C$		$C_0$		rpm		—			
7.938 $\frac{h8}{j7}$	12.700 $\frac{j7}{j7}$	7.921 $\frac{312}{j7}$	—	7.938	7.929	12.710	12.692	5 110	6 090	20 000	—		—				

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952361222
Innendurchmesser	7.938 mm
Außendurchmesser	12.7 mm
Dicke	7.92 mm
Gewicht	4 g
Verpackung	1

[kontakt@123kugellager.at](mailto:kontakt@123kugellager.at)

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE