

Nadelhülsenlager YB98-IKO - YB98-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/nadelhulsenlager/yb98-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series

Shaft dia. mm (inch)	Identification number								
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g
14.288 ($\frac{9}{16}$)	—	—	—	—	—	—	—	—	YB 98 10.1
Boundary dimensions mm(inch)		Standard mounting dimensions mm		Basic dynamic load rating		Basic static load rating		Allowable rotational speed ^(*)	
F_w	D	C	Shaft dia. h_8 Max. Min.	Housing bore dia. J_7 Max. Min.	C N	C_0 N	Allowable rotational speed ^(*) rpm	Assembled inner ring	
14.288 $\frac{9}{16}$	19.050 $\frac{3}{4}$	12.70 500	14.288 14.277	19.062 19.041	11 600	20 400	11 000	RB 68	

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952361604
Innendurchmesser	14.288 mm
Außendurchmesser	19.05 mm
Dicke	12.7 mm
Verpackung	1

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE