


Nadelhülsenlager YB2416-IKO - YB2416-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/nadelhulsenlager/yb2416-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number												
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g				
38.100 (1 1/2)	—	—	—	—	—	—	—	—	YB 2416	105			
Boundary dimensions		mm(inch)		Standard mounting dimensions				mm		Basic dynamic load rating	Basic static load rating	Allowable rotational speed ⁽¹⁾	Assembled inner ring
F_w	D	C_1	t_1	Shaft dia. mm	Housing bore dia. mm	C	C_0	C_0	N	N	rpm	IRB 2016	
38.100	47.625	25.40	—	38.100	38.084	47.639	47.614	55	100	118	000	4 000	IRB 2016

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952363110
Innendurchmesser	38.1 mm
Außendurchmesser	47.625 mm
Dicke	25.4 mm
Verpackung	1

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE