


Nadellager GBR1223520-IKO - GBR1223520-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/radial/gbri223520-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			<i>d</i>	<i>D</i>	<i>C</i>	<i>B</i>	<i>F_w</i>
34.925 (1 1/8)	GBR1 223520	316	34.925 \pm 0.015	55.562 \pm 0.030	31.750 \pm 0.020	32.000	41.275 \pm 0.020

Standard mounting dimensions mm				Basic dynamic load rating <i>C</i> N	Static load rating <i>C₀</i> N	Allowable rotational speed (1) rpm	Assembled inner ring LRBZ 222620
<i>d_a</i> Min.	<i>d_a</i> Max.	<i>D_a</i> Max.	<i>r_{as max}</i> (°)				
40.2	40.2	50.5	0.6	67 000	130 000	3 500	

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is preapplied. Perform proper lubrication.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952377490
Innendurchmesser	34.925 mm
Außendurchmesser	55.562 mm
Dicke	32 mm
Verpackung	1

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE