


Nadellager GBR364828-IKO - GBR364828-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/radial/gbr364828-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm (⁽¹⁾) Max.	
			F	D	C	D _s	r _{as max}
57.150 (2 1/4)	GBR 364828	580	57.150 (3)	76.200 (3)	44.450 (1 3/4)	69.2	1.5
Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm					
133 000	276 000	2 500					

Notes:
(1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks:
2. The outer ring has an oil groove and an oil hole.
No grease is pre-packed. Perform proper lubrication.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952377568
Innendurchmesser	57.15 mm
Innendurchmesser	2 1/4" inch
Außendurchmesser	76.2 mm
Außendurchmesser	3" inch
Dicke	44.45 mm
Dicke	1 3/4" inch
Verpackung	1

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE