


Nadellager GBR486028-IKO - GBR486028-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/radial/gbr486028-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm (⁽¹⁾) Max. $r_{as\ max}$	
			F	D	C	D_s	$r_{as\ max}$
76.200 (3)	GBR 486028	745	76.200 ⁽³⁾	95.250 ⁽³⁾⁽²⁾	44.450 ⁽¹⁾⁽²⁾	88	1.5
Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed ⁽⁴⁾					
N	N	rpm					
154 000	368 000	2 000					

Notes:
⁽¹⁾ Maximum permissible corner radius of the housing.
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
 The outer ring has an oil groove and an oil hole.
 Remarks:
 2. No grease is pre-applied. Perform proper lubrication.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952377629
Innendurchmesser	76.2 mm
Innendurchmesser	3" inch
Außendurchmesser	95.25 mm
Außendurchmesser	3 3/4" inch
Dicke	44.45 mm
Dicke	1 3/4" inch
Verpackung	1

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE