


Nadellager GBR142212-IKO - GBR142212-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/radial/gbr142212-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm (⁽¹⁾) Max.	
			F	D	C	D _s	r _{as max}
22.225 (⁽²⁾ 7/8)	GBR 142212	71	22.225 ⁽¹⁾ ₀	34.925 ⁽¹⁾ ₀	19.050 ⁽¹⁾ ₀	30	0.6
Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽³⁾					
N	N	rpm					
28 600	40 100	7 000					

Notes:
⁽¹⁾ Maximum permissible corner radius of the housing.
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
 Remarks:
 2. The outer ring has an oil groove and an oil hole.
 3. No grease is pre-packed. Perform proper lubrication.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952377711
Innendurchmesser	22.225 mm
Innendurchmesser	7/8" inch
Außendurchmesser	34.925 mm
Außendurchmesser	1 3/8" inch
Dicke	19.05 mm
Dicke	3/4" inch
Verpackung	1

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE