


Nadellager GBR243320-IKO - GBR243320-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/radial/gbr243320-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



| Shaft dia. mm (inch) | Identification number | Mass (ref.) g | Boundary dimensions mm(inch) | | | Standard mounting dimensions mm (⁽¹⁾) Max. | |
|-----------------------------------|---|---|---------------------------------|----------------|----------------|--|---------------------|
| | | | F | D | C | D _s | r _{as max} |
| 38.100 (1 1/2) | GBR 243320 | 205 | 38.100 (1 1/2) | 52.388 (2 1/4) | 31.750 (1 1/4) | 47.3 | 0.6 |
| Basic dynamic load rating C | Basic static load rating C ₀ | Allowable rotational speed ⁽²⁾ | | | | | |
| N | N | rpm | | | | | |
| 64 100 | 121 000 | 4 000 | | | | | |

Notes:
(1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks:
2. The outer ring has an oil groove and an oil hole.
3. No grease is pre-packed. Perform proper lubrication.

PRODUKTMERKMALE

| | |
|------------------|---------------|
| Marke | IKO |
| N° Ean13 | 3663952377797 |
| Innendurchmesser | 38.1 mm |
| Innendurchmesser | 1 1/2" inch |
| Außendurchmesser | 52.388 mm |
| Außendurchmesser | 2 1/16" inch |
| Dicke | 31.75 mm |
| Dicke | 1 1/4" inch |
| Verpackung | 1 |

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE