


Nadellager GBR1284824-IKO - GBR1284824-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/radial/gbri284824-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



| Shaft dia. mm (inch) | Identification number | Mass (Ref.) g | Boundary dimensions mm(inch) | | | | |
|----------------------------|--------------------------|---------------------|------------------------------|------------|----------------|--------|----------------|
| | | | d | D | C | B | F _w |
| 44.450 (1 1/2) | GBR1 284824 | 790 | 44.450 (1 1/2) | 76.200 (3) | 38.100 (1 1/2) | 38.350 | 57.150 (2 1/4) |

| Standard mounting dimensions mm | | | | Basic dynamic load C ₁₀ (*) N | Static load rating C ₀ N | Allowable rotational speed (**) rpm | Assembled inner ring LRBZ 283624 |
|------------------------------------|------------------------|------------------------|----------------------------|---|--|--|--|
| d _a Min. | d _a Max. | D _a Max. | r _{as max} (*) | | | | |
| 52.5 | 55 | 69.2 | 1.5 | 113 000 | 224 000 | 2 500 | LRBZ 283624 |

Notes: (*) Maximum permissible corner radius of the housing
(**) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-applied. Perform proper lubrication.

PRODUKTMERKMALE

| | |
|------------------|---------------|
| Marke | IKO |
| N° Ean13 | 3663952377872 |
| Innendurchmesser | 44.45 mm |
| Außendurchmesser | 76.2 mm |
| Dicke | 38.1 mm |
| Gewicht | 514 g |
| Verpackung | 1 |

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE