


# Nadellager GBRI406028-IKO - GBRI406028-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/radial/gbri406028-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			$d$	$D$	$C$	$B$	$F_w$
<b>63.500</b> (2 1/2)	<b>GBRI 406028</b>	1 230	63.500 $\pm$ 0.010	95.250 $\pm$ 0.010	44.450 $\pm$ 0.010	44.700	76.200 $\pm$ 0.010

Standard mounting dimensions mm				Basic dynamic load rating $C_0$ N	Static load rating $C_0$ N	Allowable rotational speed <sup>(*)</sup> rpm	Assembled inner ring
$d_a$ Min.	$d_a$ Max.	$D_a$ Max.	$r_{as\ max}$ ( <sup>†</sup> )				
71	73	88	1.5	154 000	368 000	2 000	<b>LRBZ 404828</b>

Notes: <sup>(†)</sup> Maximum permissible corner radius of the housing.  
<sup>(\*)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. No grease is pre-applied. Perform proper lubrication.

## PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952377940
Innendurchmesser	63.5 mm
Außendurchmesser	95.25 mm
Dicke	44.45 mm
Verpackung	1

[kontakt@123kugellager.at](mailto:kontakt@123kugellager.at)

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE