


Nadellager RNA69-32-U-IKO - RNA69-32-U-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/radial/rna69-32-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring



Shaft dia. mm	Identification number				Mass (Ref) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		F _w	D	C	r _s (1)
40	—	—	—	RNA 69/32U	170	40	52	36	0.6
Standard mounting diameter D _s Max. mm	Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed (2)						
48	50 300	88 300	5 000						

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952379159
Innendurchmesser	40 mm
Außendurchmesser	52 mm
Dicke	36 mm
Verpackung	1

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE