


# Nadellager RNA4920-U-IKO - RNA4920-U-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/radial/rna4920-u-iko>



Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		$F_w$	$D$	$C$	$r_s$ (1)
115	---	<b>RNA 4920U</b>	---	---	1 200	115	140	40	1.1
Standard rounding dimension $D_s$ Max. mm									
	Basic dynamic load rating $C$ N	Basic static load rating $C_0$ N	Allowable rotational speed (reference speed) rpm						
133.5	134 000	297 000	1 700						

Notes: (1) Minimum allowable value of chamfer dimension  $r$ .  
 (2) Allowable rotational speed applies to grease lubrication.  
 Remarks: 1. The outer ring has an oil groove and an oil hole.  
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952379852
Innendurchmesser	115 mm
Außendurchmesser	140 mm
Dicke	40 mm
Verpackung	1

[kontakt@123kugellager.at](mailto:kontakt@123kugellager.at)

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE