


Nadellager NA6916-UU-IKO - NA6916-UU-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/radial/na6916-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring



Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
80	—	—	NA 6916UU	—	1 570	80	110	54	55

r _s min (°) F _w	Standard mounting dimensions mm			Basic static load rating C ₀ N	Basic dynamic load rating C ₁₀ N	Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring LRTZ 809055
	d _s Min.	d _s Max.	D _s Max.				
1	90	85	88	105	132 000	317 000	2 000

Notes: (1) Minimum allowable value of shaft diameter r
(2) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952381848
Innendurchmesser	80 mm
Außendurchmesser	110 mm
Dicke	55 mm
Verpackung	1

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE