


Nadellager BRI102216-UU-IKO - BRI102216-UU-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/radial/bri102216-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)				
	With two seals	With one seal		d	D	C	B	
15.875 ($\frac{5}{8}$)	BRI 102216 UU		113.5	15.875 ($\frac{5}{8}$)	34.925 (1 $\frac{3}{8}$)	25.400 (1)	25.650	
F_w	Standard mounting dimensions (mm)			Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ^(*) rpm	Assembled inner ring LRBZ 101416 B	
	Min.	Max.	Max. as max. ^(*)					
22.225 ($\frac{7}{8}$)	21	21.2	29.7	0.6	21 600	26 900	9 000	

Notes: (*) Minimum allowable value of chamfer dimension r
(**) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952382500
Innendurchmesser	15.875 mm
Innendurchmesser	5/8" inch
Außendurchmesser	34.925 mm
Außendurchmesser	1 3/8" inch
Dicke	25.4 mm
Dicke	1" inch
Verpackung	1

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE