


# Nadellager BRI406028-UU-IKO - BRI406028-UU-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/radial/bri406028-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)			
	With two seals	With one seal		d	D	C	B
<b>63.500</b> (2 1/2)	<b>BRI 406028 UU</b>		1 065	63.500 (2 1/2)	95.250 (3 7/8)	44.450 (1 3/4)	44.700
$F_w$	Standard mounting dimensions (mm)		Basic dynamic load rating C N	Basic static load rating $C_0$ N	Allowable rotational speed <sup>(*)</sup> rpm	Assembled inner ring	
	Min.	Max.				$d_s$	$D_s$ as max
76.200 (3 )	71	73	105 000	211 000	2 500	<b>LRBZ 404828 B</b>	

Notes: (\*) Minimum allowable value of diameter dimension r  
(\*\*) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952382777
Innendurchmesser	63.5 mm
Außendurchmesser	95.25 mm
Dicke	44.45 mm
Verpackung	1

[kontakt@123kugellager.at](mailto:kontakt@123kugellager.at)

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE