


Nadellager GBR122016-U-IKO - GBR122016-U-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/radial/gbr122016-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		F_w	D	C
19.050 (3/4)	GBR 122016 UU		79	19.050 7/8	31.750 1 1/4	25.400 1
Standard mounting dimensions mm		Ball dynamic load rating C	Ball static load rating C_0	Allowable rotational speed ^(*)		
D_A Max.	r as max (°)	N	N	rpm		
27	0.6	26 400	34 500	4 000		

Notes: (*) Minimum allowable value of chamfer dimension r
(°) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952382876
Innendurchmesser	19.05 mm
Außendurchmesser	31.75 mm
Dicke	25.4 mm
Verpackung	1

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE