


Nadellager

GBR182620-UU-IKO - GBR182620-UU-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/radial/gbr182620-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		F_w	D	C
28.575 (1 1/4)	GBR 182620 UU		139	28.575 (1 1/4)	41.275 (1 1/2)	31.750 (1 1/4)
Standard mounting dimensions mm		Seal dynamic load rating C	Ball static load rating C_0	Allowable rotational speed ^(*)		
D_s Max.	r as max (°)	N	N	rpm		
36.3	0.6	43 900	75 300	3 000		

Notes: (*) Minimum allowable value of diameter dimension r
(°) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952382920
Innendurchmesser	28.575 mm
Außendurchmesser	41.275 mm
Dicke	31.75 mm
Verpackung	1

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE