


Nadellager TRU153320-UU-IKO - TRU153320-UU-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/radial/tru153320-uu-iko>

IKO
ROLLER BEARINGS
Caged Roller Bearings **With Seal**
Full Complement Roller Bearings **With Seal**



Shaft dia. mm	Identification number			Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type			d	D	C	r _{1,2} ⁽¹⁾	J
15	—	—	TRU 153320UU	80.5	15	33	20	0.3	19.5
	Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed n _g rpm						
27	10 400	10 400	9 500						

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
Remarks: The NAG and NAG series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
2. The bearings with seals are provided with prepacked grease.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952385853
Innendurchmesser	15 mm
Außendurchmesser	33 mm
Dicke	20 mm
Verpackung	-

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE