


# Nadellager NAU4905-UU-IKO - NAU4905-UU-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/radial/nau4905-uu-iko>

**IKO**  
**ROLLER BEARINGS**

Caged Roller Bearings [With Seal]  
Full Complement Roller Bearings [With Seal]



Shaft dis. mm	Identification number			Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type			d	D	C	r <sup>(1)</sup> min	J
25	—	NAU 4905UU		89	25	42	17	0.3	29.5
E <sub>w</sub>	Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed n <sub>g</sub> rpm						
	N	N	5 500						

Notes<sup>(\*)</sup>  
<sup>(1)</sup> Minimum allowable value of chamfer dimension r.  
<sup>(\*)</sup> Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.  
 Remarks: 1. The NAU and NUA series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.  
 2. The bearings with seals are provided with prepacked grease.

## PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952385938
Innendurchmesser	25 mm
Außendurchmesser	42 mm
Dicke	17 mm
Verpackung	1

[kontakt@123kugellager.at](mailto:kontakt@123kugellager.at)

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE