


Nadellager NAG4912-UU-IKO - NAG4912-UU-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/radial/nag4912-uu-iko>

IKO
ROLLER BEARINGS
Caged Roller Bearings [With Seal]
Full Complement Roller Bearings [With Seal]



NAG49-UU

| Shaft dis. mm | Identification number | | Mass (Ref.) g | Boundary dimensions mm | | | | |
|---------------|-----------------------------|---|---|------------------------|----|----|----------------------|----|
| | Full complement type | Caged type | | d | D | C | r ⁽¹⁾ min | J |
| 60 | NAG 4912UU | — | 425 | 60 | 85 | 25 | 1 | 67 |
| E_w | Basic dynamic load rating C | Basic static load rating C ₀ | Allowable rotational speed ⁽²⁾ | | | | | |
| 77.5 | N | N | rpm | | | | | |
| | 50 300 | 84 300 | 2 000 | | | | | |

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
Remarks: 1. The NAG and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
2. The bearings with seals are provided with prepacked grease.

PRODUKTMERKMALE

| | |
|------------------|---------------|
| Marke | IKO |
| N° Ean13 | 3663952386256 |
| Innendurchmesser | 60 mm |
| Außendurchmesser | 85 mm |
| Dicke | 25 mm |
| Verpackung | 1 |

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE