


Nadellager

NAS5011-UU-NR-IKO - NAS5011-UU-NR-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/radial/nas5011-uu-nr-iko>

IKO
ROLLER BEARINGS
Roller Bearings for Sheaves



| Shaft dia. mm | Identification number | | Mass (Ref.) kg | Boundary dimensions mm | | | | | | |
|---------------|-----------------------|-------------|----------------|------------------------|----|----------------|----|----|----------------|-----|
| | Sealed type | Shield type | | d | D | D ₂ | B | C | C ₁ | S |
| 55 | NAS 5011UU | NR | 1.15 | 55 | 90 | 94.8 | 46 | 45 | 34 | 5.5 |

| f | c | r _s mm ⁽¹⁾ | J | Basic dynamic load rating C N | Static load rating C ₀ N | Allowable rotational speed ⁽²⁾ rpm |
|-----|---|----------------------------------|----|-------------------------------|-------------------------------------|---|
| 2.5 | 2 | 0.6 | 68 | 118 000 | 193 000 | 1 800 |

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r.
⁽²⁾ Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
 Remarks: 1. The NAS and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
 2. The bearings with seals are provided with prepacked grease.

PRODUKTMERKMALE

| | |
|------------------|---------------|
| Marke | IKO |
| N° Ean13 | 3663952386805 |
| Innendurchmesser | 55 mm |
| Außendurchmesser | 90 mm |
| Dicke | 46 mm |
| Verpackung | 1 |

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE