


# Nadellager

## NAS5056-ZZ-NR-IKO - NAS5056-ZZ-NR-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/radial/nas5056-zz-nr-iko>

**IKO**  
**ROLLER BEARINGS**  
Roller Bearings for Sheaves



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						
	Sealed type	Shield type		d	D	D <sub>2</sub>	B	C	C <sub>1</sub>	S
280		NAS 5056ZZNR	90.9	280	420	440	190	189	154	17.5

f	c	r <sub>s</sub> mm <sup>(1)</sup>	J	Basic dynamic load rating C N	Static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(2)</sup> rpm
7	5	2	335	2 210 000	4 860 000	350

Notes<sup>(\*)</sup>  
<sup>(1)</sup> Minimum allowable value of chamfer dimension r  
<sup>(2)</sup> Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.  
 Remarks: 1. The NAS and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.  
 2. The bearings with seals are provided with prepacked grease.

### PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952387253
Innendurchmesser	280 mm
Außendurchmesser	420 mm
Dicke	190 mm
Verpackung	1

[kontakt@123kugellager.at](mailto:kontakt@123kugellager.at)

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE