

Nadellager NAX6040Z-IKO - NAX6040Z-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/radial/nax6040z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS
Needle Roller Bearings with Thrust Ball Bearing Without Inner Ring
Needle Roller Bearings with Thrust Roller Bearing Without Inner Ring

Shaft dia. mm	Identification number					
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g
60		NAX 6040Z	454	---	---	---
Boundary dimensions mm						
F_w	D	D_1	D_2	L	H	r
60	72	85	86.5	40	17	12
Basic ratings						
Basic rating C		Basic static load rating C_0		Allowable rotational speed ⁽¹⁾		
Radial	Axial	Radial	Axial	rpm		
N	N	N	N	47 500	41 400	103 000
				89 700		4 000

Notes:
(1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
Remarks:
1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952390376
Innendurchmesser	60 mm
Außendurchmesser	72 mm
Dicke	40 mm
Verpackung	1

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE