

# Nadellager NBX6040Z-IKO - NBX6040Z-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/radial/nbx6040z-iko>

**IKO**

**COMBINED TYPE NEEDLE ROLLER BEARINGS**

Needle Roller Bearings with Thrust Ball Bearing Without Inner Ring  
Needle Roller Bearings with Thrust Roller Bearing Without Inner Ring

Identification number										
Shaft dia. mm	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g				
60	---	---	---	---	---	---	<b>NBX 6040Z</b>			538
Boundary dimensions mm										
$F_w$	$D$	$D_1$	$D_2$	$L$	$H$	$r_1$ min.	$d_f$	Basic load rating $C$	Basic static load rating $C_0$	Allowable rotational speed <sup>(2)</sup>
60	72	85	86.5	40	17	1	60	47 500	64 600	103 000
								Basic dynamic load rating $C$		Allowable rotational speed <sup>(2)</sup>
								Radial	Axial	rpm
								N	N	4 000
								Basic static load rating $C_0$		Allowable rotational speed <sup>(2)</sup>
								Radial	Axial	rpm
								N	N	4 000

Notes:  
(1) Minimum allowable value of chamfer dimension  $r$ .  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.

Remarks:  
1. The outer ring has an oil groove and an oil hole.  
2. Grease is not prepacked. Perform proper lubrication.

## PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952390529
Innendurchmesser	60 mm
Außendurchmesser	72 mm
Dicke	40 mm
Verpackung	1
Standard	Ohne Standard

[kontakt@123kugellager.at](mailto:kontakt@123kugellager.at)

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE