

Nadellager NAX7040Z-IKO - NAX7040Z-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/radial/nax7040z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS
Needle Roller Bearings with Thrust Ball Bearing Without Inner Ring
Needle Roller Bearings with Thrust Roller Bearing Without Inner Ring

Identification number										
Shaft dia. mm	Mass (Ref.) g		With dust cover		Mass (Ref.) g		With dust cover		Mass (Ref.) g	
70	NAX 7040Z		606		—		—		—	
Boundary dimensions mm										
F_w	D	D_1	D_2	L	H	r_1 min.	d_f	Basic load ratings C	Basic static load rating C_0	Allowable rotational speed ⁽²⁾
70	85	95	96.5	40	18	1	70	Radial: 55 500 Axial: 43 100	Radial: 120 000 Axial: 101 000	3 500 rpm

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952390550
Innendurchmesser	70 mm
Außendurchmesser	85 mm
Dicke	40 mm
Verpackung	1

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE