

Nadellager NAXI723Z-IKO - NAXI723Z-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/radial/naxi723z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number								
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g	d	D	D ₁
7		NAXI 723Z	45	—	—	—	7	19	24

Boundary dimensions mm				Bore diameter mm	Basic dynamic load rating C	Basic static load rating C ₀		Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring						
D ₂	L	B	H			Radial	Axial			Radial	Axial				
25	23	16	9	6.5	0.3	0.2	10	18	9	8 230	10 000	9 190	11 100	9 500	LRT 71016

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r.
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
 Remarks: 1. The outer ring has an oil groove and an oil hole.
 2. Grease is not prepacked. Perform proper lubrication.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952390574
Innendurchmesser	7 mm
Außendurchmesser	19 mm
Dicke	23 mm
Verpackung	1

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE