

Nadellager NAXI923-IKO - NAXI923-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/radial/naxi923-iko>

LINEAR TYPE NEEDLE ROLLER BEARINGS

Needle Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Bearings with Thrust Roller Bearing **With Inner Ring**

Identification number														
		Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g			<i>d</i>				
NAXI	923	49.5	—	—	—	—	—			9				
Boundary dimensions mm		Bore diameter mm		Basic dynamic load rating C		Basic static load rating C ₀		Allowable rotational speed ⁽¹⁾	Assemble					
<i>B</i>	<i>H</i>	<i>I</i> ₁	<i>r</i> _{max}	<i>r</i> _{min}	Radial	Axial	Radial	Axial	rpm					
16	9	6.5	0.3	0.3	12	12	20	11	9 250	9 670	11 200	11 100	9 000	LRT

(1) Minimum allowable value of chamfer dimension *r*. Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in IAX series, and a maximum of 25% of this value is allowable in the NBSX series. The outer ring has an oil groove and an oil hole. Grease is not prepacked. Perform proper lubrication.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952390666
Innendurchmesser	9 mm
Außendurchmesser	21 mm
Dicke	23 mm
Verpackung	1

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE