

Nadellager NAXI1223Z-IKO - NAXI1223Z-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/radial/naxi1223z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number									
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	d	D	D ₁
12		NAXI 1223Z	56.5	—	—	—	—	12	24	28

Boundary dimensions mm										Basic dynamic load rating C	Basic static load rating C ₀		Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring			
D ₂	L	B	H	I ₁	r _{max}	r _{min}	d ₁	d ₂	d ₃		Radial	Axial			Radial	Axial	
25	23	16	9	6.5	0.3	0.2	10	10	18	9	8	230	10 000	9 190	11 100	9 500	LRT 71016

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.

Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952390697
Innendurchmesser	12 mm
Außendurchmesser	24 mm
Dicke	23 mm
Verpackung	1

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE