

# Nadellager NBXI1425-IKO - NBXI1425-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/radial/nbxi1425-iko>

**IKO**  
**COMBINED TYPE NEEDLE ROLLER BEARINGS**

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**  
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number						d	D	D <sub>1</sub>
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g			
14	---	---	<b>NBXI 1425</b>	70.5	---	---	14	26	30

Boundary dimensions mm			r <sup>(1)</sup>	r <sub>max</sub> <sup>(2)</sup>	r <sub>min</sub> <sup>(2)</sup>	d <sub>4</sub>	d <sub>5</sub>	Basic dynamic load rating C		Basic static load rating C <sub>0</sub>		Allowable rotational speed <sup>(3)</sup> rpm	Assembled inner ring LRT 141717		
D <sub>2</sub>	L	H						Radial	Axial	Radial	Axial				
31	25	17	9	8	0.3	0.3	17	28	16	12 900	11 400	16 300	28 600	13 000	LRT 141717

Notes:  
(1) Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.  
Remarks:  
1. The outer ring has an oil groove and an oil hole.  
2. Grease is not prepacked. Perform proper lubrication.

## PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952390741
Innendurchmesser	14 mm
Außendurchmesser	26 mm
Dicke	25 mm
Verpackung	1

[kontakt@123kugellager.at](mailto:kontakt@123kugellager.at)

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE