

Nadellager NAXI1730Z-IKO - NAXI1730Z-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/radial/naxi1730z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number										
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g	d	D	D ₁		
17			NAXI 1730Z	103	—	—	—	—	17	30	35

Boundary dimensions mm				Bore chamfer radius mm	Basic dynamic load rating C	Basic static load rating C ₀		Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring							
D ₂	L	B	H			Radial	Axial			Radial	Axial					
36	30	20.5	10	10.5	0.3	0.3	20	29	19	17	600	14 200	25 400	19 700	7 500	LRT 172020

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r.
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
 Remarks: 1. The outer ring has an oil groove and an oil hole.
 2. Grease is not pre-packed. Perform proper lubrication.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952390772
Innendurchmesser	17 mm
Innendurchmesser	0.669" inch
Außendurchmesser	30 mm
Außendurchmesser	1.181" inch
Dicke	30 mm
Dicke	1.181" inch
Verpackung	1

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE