

Nadellager NBXI2030Z-IKO - NBXI2030Z-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/radial/nbxi2030z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number								d	D	D _i
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g			
20	---	---	---	---	NBXI 2030Z	175	---	20	37	42	

Boundary dimensions mm				Bore diameter mm	Bore diameter mm	Basic dynamic load rating C	Basic static load rating C ₀		Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring					
D ₂	L	B	H				Radial	Axial			Radial	Axial			
43	30	20.5	11	9.5	0.6	0.3	25	40	24	20 000	22 700	32 100	60 700	9 000	LRT 202520

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.
Remarks: The outer ring has an oil groove and an oil hole.
Z: Grease is not prepacked. Perform proper lubrication.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952390833
Innendurchmesser	20 mm
Außendurchmesser	37 mm
Dicke	30 mm
Verpackung	1

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE