

## Nadellager NBXI2530Z-IKO - NBXI2530Z-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/radial/nbxi2530z-iko>

**LINEAR TYPE NEEDLE ROLLER BEARINGS**

Needle Bearings with Thrust Ball Bearing **With Inner Ring**  
Needle Bearings with Thrust Roller Bearing **With Inner Ring**

Identification number																		
Mass (Ref.) g		With dust cover		Mass (Ref.) g		Mass (Ref.) g		With dust cover		Mass (Ref.) g		$d$						
—		—		—		—		—		—		25						
<b>NBXI 2530Z</b>																		
Boundary dimensions mm				Bore diameter mm		Basic dynamic load rating C				Basic static load rating C <sub>0</sub>		Allowable rotational speed <sup>(2)</sup> rpm	Assemble					
$B$	$H$	$I_1$	$r_{max}$	$d_{min}$	$d_{max}$	Radial	Radial	Radial	Radial	Radial	Radial							
20.5	11	9.5	0.6	0.3	30	45	29	25	100	27	400	40	100	81	000	8	000	LRT

Minimum allowable value of chamfer dimension r  
Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in IAX series, and a maximum of 25% of this value is allowable in the NBXI series.  
The outer ring has an oil groove and an oil hole.  
Grease is not prepacked. Perform proper lubrication.

### PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952390871
Innendurchmesser	25 mm
Außendurchmesser	42 mm
Dicke	30 mm
Verpackung	1

[kontakt@123kugellager.at](mailto:kontakt@123kugellager.at)

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE