

# Nadellager NAXI3030Z-IKO - NAXI3030Z-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/radial/naxi3030z-iko>

**IKO**  
**COMBINED TYPE NEEDLE ROLLER BEARINGS**

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**  
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number						d	D	D <sub>1</sub>
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover			
30		<b>NAXI 3030Z</b>	215	—	—	—	30	47	52

  

Boundary dimensions mm				Bore diameter mm	Basic dynamic load rating C	Basic static load rating C <sub>0</sub>		Allowable rotational speed <sup>(1)</sup> rpm	Assembled inner ring	
D <sub>2</sub>	L	B	H			Radial	Radial			Axial
53	30	20	12	9	26 900	21 200	46 200	37 600	6 000	LRT 303520

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimension r.  
<sup>(2)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.  
 Remarks: 1. The outer ring has an oil groove and an oil hole.  
 2. Grease is not prepacked. Perform proper lubrication.

## PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952390888
Innendurchmesser	30 mm
Außendurchmesser	47 mm
Dicke	30 mm
Verpackung	1

[kontakt@123kugellager.at](mailto:kontakt@123kugellager.at)

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE