

Nadellager NAXI3532-IKO - NAXI3532-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/radial/naxi3532-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number						d	D	D _i
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover			
35	NAXI 3532	265	—	—	—	—	35	52	60
Boundary dimensions mm									
D ₂	L	B	H	I ₁	r ⁽¹⁾	r _{max} ⁽²⁾	r _{min} ⁽²⁾	d ₄	d ₅
61	32	20	13	10	0.6	0.3	40	52	39
Load ratings									
Basic dynamic load rating C		Basic static load rating C ₀		Allowable rotational speed ⁽³⁾		Assembled inner ring			
Radial		Radial		rpm		LRT 354020			
N		N		N					
29 400		26 900		54 100		50 000		5 500	

Notes:
(1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
Remark 1: The outer ring has an oil groove and an oil hole.
2: Grease is not prepacked. Perform proper lubrication.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952390925
Innendurchmesser	35 mm
Außendurchmesser	52 mm
Dicke	32 mm
Verpackung	1

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE