

# Nadellager NBXI4032Z-IKO - NBXI4032Z-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/radial/nbxi4032z-iko>

**IKO**  
**COMBINED TYPE NEEDLE ROLLER BEARINGS**

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**  
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number								d	D	D <sub>1</sub>
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover			
40	---	---	---	---	<b>NBXI 4032Z</b>	353	---	40	58	65	

Boundary dimensions mm				Bore chamfer mm	Bore chamfer mm	Basic dynamic load rating C	Basic static load rating C <sub>0</sub>		Allowable rotational speed <sup>(1)</sup> rpm	Assembled inner ring					
D <sub>2</sub>	L	B	H				Radial	Radial			Radial	Radial			
66.5	32	20	14	9	0.6	0.3	45	62	44	31 000	40 800	60 200	133 000	5 500	LRT 404520

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.  
Remarks: The outer ring has an oil groove and an oil hole.  
Z: Grease is not prepacked. Perform proper lubrication.

## PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952390994
Innendurchmesser	40 mm
Außendurchmesser	58 mm
Dicke	32 mm
Verpackung	1

[kontakt@123kugellager.at](mailto:kontakt@123kugellager.at)

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE