

Nadellager NBXI4535Z-IKO - NBXI4535Z-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/radial/nbxi4535z-iko>

IKO

COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing

With Inner Ring

Needle Roller Bearings with Thrust Roller Bearing

With Inner Ring

Identification number

Shaft dia. mm	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g	d	D	D ₁
45	---	---	---	---	---	---	45	62	70

NBXI 4535Z

396

45

62

70

Boundary dimensions mm					Basic dynamic load rating C					Basic static load rating C ₀					Allowable rotational speed ⁽¹⁾					Assembled inner ring				
D ₂	L	B	H	I ₁	(²) r _{max}	(²) r _{min}	d ₁	d ₂	d ₃	Radial	Axial	Radial	Axial		rpm									
71.5	35	25	14	10	0.6	0.3	50	50	67	49	42	200	43	300	83 400	148 000	5 000			LRT	455025			

Notes:
 (1) Minimum allowable value of chamfer dimension r.
 (2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.
 The outer ring has an oil groove and an oil hole.

Remark 1: Grease is not prepacked. Perform proper lubrication.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952391038
Innendurchmesser	45 mm
Außendurchmesser	62 mm
Dicke	35 mm
Verpackung	1

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE