

Nadellager NAXI5040-IKO - NAXI5040-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/radial/naxi5040-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

| Identification number | | | | | | | | | | | | | |
|-----------------------------|------------------|-----------|-----------------|----------------|------------------|------------------|------------------|----------------|------------------|---|----------------------|--|-------|
| Shaft dia. mm | Mass (Ref.) g | | With dust cover | | Mass (Ref.) g | | With dust cover | | Mass (Ref.) g | d | D | D ₁ | |
| | 50 | NAXI 5040 | 582 | | | | | | | | | | |
| Boundary dimensions mm | | | | | | | | | | | | | |
| D ₂ | L | B | H | I ₁ | r ⁽¹⁾ | r ⁽²⁾ | r ⁽³⁾ | d ₄ | d ₅ | d | Assembled inner ring | | |
| 86.5 | 40 | 25.5 | 17 | 12 | 1 | 1 | 60 | 60 | 75 | 59 | 47 500 | 41 400 | |
| Basic dynamic load rating C | | | | | | | | | | Basic static load rating C ₀ | | Allowable rotational speed ⁽²⁾ rpm | |
| Radial | | | | | Axial | | | | | Radial | | | Axial |
| N | | | | | N | | | | | N | | N | |
| 89 700 | | | | | | | | | | 4 000 | | LRT 506025 | |

Notes:
(1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
Remarks:
1. The outer ring has an oil groove and an oil hole.
2. Grease is not pre-packed. Perform proper lubrication.

PRODUKTMERKMALE

| | |
|------------------|---------------|
| Marke | IKO |
| N° Ean13 | 3663952391045 |
| Innendurchmesser | 50 mm |
| Innendurchmesser | 1.969" inch |
| Außendurchmesser | 72 mm |
| Außendurchmesser | 2.835" inch |
| Dicke | 40 mm |
| Dicke | 1.575" inch |
| Verpackung | 1 |

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE