

Nadellager NAXI6040-IKO - NAXI6040-IKO

<https://www.123kugellager.at/kugellager-gehauselager/nadellager/radial/naxi6040-iko>

IKO

COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing

With Inner Ring

Needle Roller Bearings with Thrust Roller Bearing

With Inner Ring

NAXI

Identification number

Shaft dia. mm	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g	d	D	D ₁
60	NAXI 6040	750	—	—	—	—	60	85	95

Boundary dimensions mm										Basic dynamic load rating C		Basic static load rating C ₀		Allowable rotational speed ⁽²⁾		Assembled inner ring		
D ₂	L	B	H	I ₁	(1)	(2)	r _{max}	r _{min}	d ₁	d ₂	d ₃	Radial	Axial	Radial	Axial	rpm		
96.5	40	25.5	18	11	1	1	70	70	85	68	55	500	43	100	120 000	101 000	3 500	LRT 607025

Notes (1) Minimum allowable value of chamfer dimension r.

(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.

Remark 1. The outer ring has an oil groove and an oil hole.

2. Grease is not pre-packed. Perform proper lubrication.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952391083
Innendurchmesser	60 mm
Außendurchmesser	85 mm
Dicke	40 mm
Verpackung	1

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE