

Gelenkköpfe TAPR GIHO-KL-16DO-DURBAL - GIHO-KL-16DO-DURBAL

<https://www.123kugellager.at/kugellager-gehauselager/gelenkkopfe-gelenklager/tapr/giho-kl-16do-durbal>

GIHO-KL-16DO



Description: Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE- ES pressed into rod end housing. Sliding combination steel/steel with grease nipple.

female thread: hydraulic rod ends, according to DIN 24555

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

* without grease nipple

| order number | measurement [mm] | | | | | | | | | |
|-------------------|------------------|----|----------------|----------------|-------------|----------------|----------------|----|----------------|----------------|
| right hand thread | left hand thread | d | d ₁ | d ₂ | G | d ₄ | d ₅ | B | C ₁ | C ₂ |
| GIHO-KL 16 DO* | | 16 | 20,7 | 45 | M 12 x 1,25 | 21 | 45 | 14 | 11 | 13 |

| type | measurement [mm] | | | | α [°] | load rating C ₀ [kN] | weight [kg] |
|------------------------|------------------|----------------|----------------|----------------|-------|---------------------------------|-------------|
| | h ₁ | l ₁ | l ₂ | l ₃ | | | |
| GIHO-K / GIHO-KL 16 DO | 48 | 17 | 70,5 | 20 | 10 | 28,5 | 0,22 |

PRODUKTMERKMALE

| | |
|------------------|---------------|
| Marke | DURBAL |
| N° Ean13 | 3663952500645 |
| Innendurchmesser | 16 mm |
| Außendurchmesser | 45 mm |
| Dicke | 11 mm |
| Typ | TAPR |
| Gewicht | 220 g |
| Gewinde | Linksgewinde |
| Schmierung | mit |
| Verpackung | 1 |

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE