

# Gelenkköpfe SI

## BRTF16-03-501-DURBAL - BRTF16-03-501-DURBAL

<https://www.123kugellager.at/kugellager-gehauselager/gelenkkopfe-gelenklager/si/brtf16-03-501-durbal>

### BRTF16-03-501



**rod end housing:**  
forged steel, case-hardened bearing race, superfinished, surface galvanized, free of Cr VI

**inner ring:**  
ball bearing steel, hardened, superfinished

**lubrication:**  
aluminium complex soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

**lubrication fitting:**  
DIN 71 412 H1

**bearing clearance:**  
10 - 30 µm radial

**tolerances:**  
see page 10

**DURBAL® heavy-duty rod ends with integral self-aligning roller bearing**

**female thread:**  
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K

order number		measurements [mm]									
type	right hand thread	left hand thread	d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>	d <sub>5</sub>	d <sub>6</sub>	d <sub>7</sub>	h <sub>1</sub>	h <sub>2</sub>
BRTF 16 -03	-501		16	22,0	M 16	19,0	42	27	21	15	
measurements [mm]		weight	rotational speed limit		basic load rating		stat.				
type	h	l	l <sub>1</sub>	l <sub>2</sub>	SW	α [°]	[kg]	n <sub>max</sub> [min <sup>-1</sup> ]	C [N]	C <sub>0</sub> [N]	
BRTF 16	64	28	8,0	22	22	7,0	0,220	975	13300	8900	

## PRODUKTMERKMALE

Marke	DURBAL
N° Ean13	3663952506852
Innendurchmesser	16 mm
Außendurchmesser	42 mm
Dicke	21 mm
Typ	SI
Gewicht	220 g
Gewinde	Rechtsgewinde
Schmierung	mit
Verpackung	1

[kontakt@123kugellager.at](mailto:kontakt@123kugellager.at)

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE