


Winkelgelenke SA

BRM12-00-502-DURBAL - BRM12-00-502-DURBAL

<https://www.123kugellager.at/kugellager-gehauselager/gelenkkopfe-gelenklager/sa/brm12-00-502-durbal>

BRM12-00-502



male thread:
long-term
lubrication,
low maintenance,
shields,
adapter sizes
according to
DIN ISO 12240-4,
series K

**DURBAL® heavy-duty rod ends
with integral self-aligning
ball bearing**

rod end housing:
forged steel, case-hardened bearing race,
superfinished, rolled thread, surface gal-
vanized, free of Cr-VI

inner ring:
self-bearing steel, hardened,
superfinished

lubrication:
aluminum-complex-soap-grease,
temperature range -45 °C to +120 °C,
approval according to USDA H1

lubrication fitting:
DIN 2455 D11A (sizes 6 to 10)
DIN 21 412 H1 (sizes 12 to 30)

bearing clearance:
10 - 30 µm radial
tolerances:
see page 10

order number		measurements [mm]									
Type	right-hand thread	M 12	d ₁	d ₂	d ₃	d ₄	d ₅	l ₁	l ₂	l ₃	h
BRM 12 -00	-502		12	M 12		14,5	32	16		12,0	54
measurements [mm]		weight	calculation-factors		rotational speed limit	basic load rating					
Type	l	l ₃	α [°]	Y	v ₀	C	C ₀	d _{yn.}	stat.	C ₀	stat.
BRM 12	33	19	7,5			1,74	1,82	1125	4950	1800	

PRODUKTMERKMALE

Marke	DURBAL
N° Ean13	3663952506982
Innendurchmesser	12 mm
Außendurchmesser	32 mm
Dicke	16 mm
Typ	SA
Gewicht	87 g
Gewinde	Linksgewinde
Schmierung	mit
Verpackung	-
Standard	Ohne Standard

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE