

Winkelgelenke SA PM05-01-501-DURBAL - PM05-01-501-DURBAL

<https://www.123kugellager.at/kugellager-gehauselager/gelenkkopfe-gelenklager/sa/pm05-01-501-durbal>

PM05-01-501



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

| order number | | measurements [mm] | | | measurements [mm] | | | weight | | | rotational speed limit | | | basic load rating | |
|--------------|------|-------------------|---------|-----|-------------------|----|----|--------|----|--------|------------------------|------|--------------|-------------------|--------|
| type | type | d1 | d2 | d3 | d4 | d5 | d7 | b1 | b2 | weight | Y | Yc | nmax [min-1] | C [N] | C0 [N] |
| PM 05 -01 | -501 | 5 | M 8 x 1 | 7.5 | 19 | 12 | 12 | 12 | 8 | 0,033 | 1,51 | 1,58 | 1350 | 1610 | 480 |

PRODUKTMERKMALE

| | |
|------------------|---------------|
| Marke | DURBAL |
| N° Ean13 | 3663952507453 |
| Innendurchmesser | 5 mm |
| Außendurchmesser | 19 mm |
| Dicke | 12 mm |
| Typ | SA |
| Gewicht | 33 g |
| Gewinde | Rechtsgewinde |
| Schmierung | mit |
| Verpackung | 1 |

kontakt@123kugellager.at

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE