

## Winkelgelenke SA PM06-00-502-DURBAL - PM06-00-502-DURBAL

<https://www.123kugellager.at/kugellager-gehauselager/gelenkkopfe-gelenklager/sa/pm06-00-502-durbal>

### PM06-00-502



**male thread:**  
long-term lubrication, low maintenance, shields

**DURBAL® heavy-duty rod ends with integral self-aligning ball bearing**

**rod end housing:**  
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

**inner ring:**  
ball bearing steel, hardened, superfinished

**lubrication:**  
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

**lubrication fitting:**  
DIN 3405 D1/A

**bearing clearance:**  
10 - 30 µm radial

**tolerances:**  
see page 10

order number		measurements [mm]					measurements [mm]					weight		calculation factors		rotational speed limit		basic load rating	
type	type	d1	d2	d3	d4	d5	d7	b1	b2	b3	Y	Yc	nmax [min <sup>-1</sup> ]	C [N]	C0 [N]	dyn.	stat.	C0	C0
PM 06 -00	-502	6	M 10 x 1	8,5	24	14	14	14	10										
type		l1	l2	l3	h1	h2	u	z	alpha [°]										
PM 06		42,5	17	64	1,5	2,5	10,5	0,062		1,28	1,34	1300	2445	765					

## PRODUKTMERKMALE

Marke	DURBAL
N° Ean13	3663952507477
Innendurchmesser	6 mm
Innendurchmesser	0.236" inch
Außendurchmesser	24 mm
Außendurchmesser	0.945" inch
Dicke	14 mm
Dicke	0.551" inch
Typ	SA
Gewicht	62 g
Gewinde	Linksgewinde
Schmierung	mit
Verpackung	1

[kontakt@123kugellager.at](mailto:kontakt@123kugellager.at)

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE